## IN THE CLAIMS:

 (Currently Amended) A method of encrypting information, the method comprising:

in a first pipeline stage:

obtaining a value A from an array having a plurality of values, wherein
each of the values is stored in a corresponding one of a plurality of
storage locations; and

determining a value B based on the value A;

and

in a second pipeline stage:

obtaining a value V from a position in the array that is based on the value A and the value B;

exclusive ORing the value V with a data value that forms a portion of the information;

## wherein the method further comprises:

shifting the array to enable the value A to be obtained from the same one of the plurality of storage locations in the array for each iteration; and

obtaining the value A from the same one of the plurality of storage locations for each iteration.

- (Original) The method as recited in claim 1, wherein the array is initialized using an encryption key sequence.
- 3. (Original) The method as recited in claim 1, wherein a first iteration of said obtaining and said exclusive ORing in the second pipeline stage is performed simultaneously with a second iteration of said obtaining and said determining in the first pipeline stage

- 4. (Original) The method as recited in claim 3, wherein the first iteration is based on a first value A in said array and wherein the second iteration is based on a next value A in said array.
- (Original) The method as recited in claim 3 further comprising incrementing an index value i during each iteration.
- (Original) The method as recited in claim 5 further comprising resetting the index value i to zero responsive to reaching a pre-determined limit.
- (Original) The method as recited in claim 6, wherein the pre-determined limit is 256.
- (Original) The method as recited in claim 6 further comprising incrementing the index value i during each iteration prior to said resetting.
- (Original) The method as recited in claim 1, wherein each of the plurality of values is stored in a storage location comprising flip-flops.
- (Cancelled).
- 11. (Original) The method as recited in claim 9, wherein the first pipeline stage includes a first sub-stage and a second sub-stage, wherein obtaining the value A is performed in the first sub-stage and said determining the value B is determined in the second sub-stage.
- 12. (Original) The method as recited in claim 9, wherein the second pipeline stage includes a third sub-stage and a fourth sub-stage, wherein an index value g based on the value A and the value B and the value V is determined in the third sub-stage, and said exclusive ORing is performed in the fourth sub-stage.

- 13. (Original) The method as recited in claim 9, wherein the second pipeline stage includes a third sub-stage and a fourth sub-stage, wherein an index value g based on the value A and the value B is determined in the third sub-stage and wherein the value V and said exclusive ORing is performed in the fourth sub-stage.
- (Withdrawn) The method as recited in claim 1, wherein the array is stored in one or more register files.
- 15. (Withdrawn) The method as recited in claim 14, wherein the first pipeline stage includes a first substage and a second substage, wherein said obtaining the value A is performed in the first substage and said determining the value B is performed in the second substage.
- 16. (Withdrawn) The method as recited in claim 15 further comprising performing a swap operation in the second sub-stage, wherein the swap operation comprises switching the locations of the value A and the value B.
- 17. (Withdrawn) The method as recited in claim 14, wherein the first pipeline stage includes a first sub-stage and a second sub-stage, wherein said obtaining the value A is performed in the first sub-stage and said determining the value B is performed in the second sub-stage.
- 18. (Withdrawn) The method as recited in claim 17, wherein the second pipeline stage includes a third substage and a fourth substage, wherein an index value g based on the value A and the value B and a value V based on the value g is determined in the third substage, and wherein said XORing is performed in the fourth substage.
- 19. (Original) The method as recited in claim 1, wherein obtaining the value B comprises determining an index f based on the value A, wherein the value B is the f<sup>th</sup> element of the array.

- (Original) The method as recited in claim 19, wherein determining a value for the index j comprises calculating the sum of j + A.
- 21. (Original) The method as recited in claim 1, wherein obtaining the value V comprises determining the sum of the value A and the value B and reading the g<sup>th</sup> element of the array, wherein g is the sum of the value A and the value B.
- 22. (Original) An encryption apparatus comprising:
  - a plurality of storage locations configured to store an array;
  - a first logic unit configured to read a value A from the array and determine a value B based on the value A; and
  - a second logic unit configured to read a value V from a position in the array that is based on the value A and the value B and to exclusive OR the value V with a data value that forms a portion of information that is to be encrypted;
  - wherein the first logic unit comprises a first pipeline stage and the second logic unit comprises a second pipeline stage;
  - wherein the encryption apparatus is further configured to:
    - shift the array to within the plurality of storage locations to enable the value A to be read from the same one of the plurality of storage locations for each iteration; and
    - read the value A from the same one of the plurality of storage locations for each iteration.
- (Original) The encryption apparatus as recited in claim 22 wherein the encryption
  apparatus is coupled to receive an encryption key sequence to initialize the array.
- 24. (Original) The encryption apparatus as recited in claim 22, wherein the second pipeline stage is configured to read the value V from the position in the array that is based on the value A and the value B and to exclusive OR the value V with a

data value simultaneously with the first pipeline stage a second iteration of reading the value A from the array and calculate a value B based on the value A.

- 25. (Original) The encryption apparatus as recited in claim 24, wherein the first iteration is based on a first value A in said array and wherein the second iteration is based on a next value A in said array.
- 26. (Original) The encryption apparatus as recited in claim 24, wherein the encryption apparatus is further configured to increment an index value i during each iteration.
- 27. (Original) The encryption apparatus as recited in claim 26, wherein the encryption apparatus is configured to reset the index value i to zero responsive to the index value reaching a predetermined limit.
- (Original) The encryption apparatus as recited in claim 27, wherein the predetermined limit is 256.
- 29. (Original) The encryption apparatus as recited in claim 27, wherein the encryption device is configured to increment the index value i during each iteration prior to resetting.
- (Original) The encryption apparatus as recited in claim 22, wherein each of the plurality of storage locations includes flip-flops.
- (Cancelled).
- 32. (Original) The encryption apparatus as recited in claim 30, wherein the first pipeline stage includes a first sub-stage and a second sub-stage, wherein obtaining the value A is performed in the first sub-stage and said determining the value B is determined in the second sub-stage.

- 33. (Original) The encryption apparatus as recited in claim 30, wherein the second pipeline stage includes a third sub-stage and a fourth sub-stage, wherein an index value g based on the value A and the value B and a value V based on the value g are determined in the third sub-stage, and wherein said exclusive ORing is performed in the fourth sub-stage.
- 34. (Withdrawn) The encryption apparatus as recited in claim 22, wherein each of the plurality of storage locations is a location in a register file.
- 35. (Withdrawn) The encryption apparatus as recited in claim 34, wherein the first pipeline stage includes a first substage and a second substage, wherein said obtaining the value A is performed in the first substage and said determining the value B is performed in the second substage.
- 36. (Withdrawn) The encryption apparatus as recited in claim 35, wherein the second sub-stage is configured to perform a swap operation, wherein the swap operation comprises switching the locations of the value A and the value B.
- 37. (Withdrawn) The encryption apparatus as recited in claim 34, wherein the first pipeline stage includes a first sub-stage and a second sub-stage, wherein the first sub-stage is configured to obtain the value A, and wherein the second sub-stage is configured to determine the value B, and wherein the second pipeline stage includes a third substage and a fourth substage, wherein the third substage is configured to determine the value V and wherein the fourth substage is configure to perform said exclusive ORing..
- 38. (Original) The encryption apparatus as recited in claim 22, wherein the first logic unit is configured to determine an index value f based on the value A, wherein the value B is the f<sup>th</sup> element of the array.

- (Original) The encryption apparatus as recited in claim 38, wherein the first logic unit is configured to determine the index value j based on the sum of j + A.
- 40. (Original) The encryption apparatus as recited in claim 38, wherein the encryption apparatus is further configured to calculate an index value g, wherein the index value g is the sum of the value A and the value B, and wherein V is the g<sup>th</sup> element of the array.
- 41. (Withdrawn) A method comprising:

reading a value A from a position in an array having a plurality of elements; reading a value B from a position in the array, wherein a position in the array of the value B is based on the value A;

writing the value A into the array position from which the value B was read;
writing the value B into the array position from which the value A was read;
shifting the array such that each value stored in a position of the array is moved to
another position in the array; and

repeating said reading a value A, said reading a value B, said writing the value A, writing the value B, and said shifting, for two or more iterations, wherein position in the array from where the value A is read is the same for each iteration.

- (Withdrawn) The method as recited in claim 41 further comprising generating a value V based on the value A and the value B.
- 43. (Withdrawn) The method as recited in claim 41, wherein each of the plurality of elements in the array is associated with an index i, wherein the value A is read from the array position where i = 0 for each iteration.
- 44. (Withdrawn) The method as recited in claim 41, wherein each of the plurality of elements is associated with an index j, and wherein the value B is read from the f<sup>th</sup>

position of the array, wherein calculating the index j comprises the equation j = j + A - 1.

- 45. (Withdrawn) The method as recited in claim 44, wherein the index j is calculated by the equation j = j + A + K[i] − 1, wherein K[i] is an i<sup>th</sup> key element of a key sequence.
- 46. (Withdrawn) The method as recited in claim 41, wherein each of the plurality elements is associated with an index g, wherein calculating the index g comprises the equation g = A + B i.
- 47. (Withdrawn) The method as recited in claim 41, wherein said shifting the array is performed subsequent to said writing the value A and said writing the value B.
- 48. (Withdrawn) The method as recited in claim 41, wherein said shifting the array is performed subsequent to said reading the value B and prior to said writing the value A and said writing the value B.
- 49. (Withdrawn) The method as recited in claim 41, wherein said shifting the array is performed subsequent to said reading the value A and prior to said reading the value B.